



Golf Cart 2S/4S

Specifications

Seating Capacity	1 + (1/3)
LxBxH (mm)	2700x1200x1950
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	145x80x12
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	3000 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Golf Cart 6S/4S Front Facing

Specifications

Seating Capacity	1 + (3/5)
LxBxH (mm)	3500x1200x1950
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	145x80x12
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	4500 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Golf Cart 8S/6S Front Facing

Specifications

Seating Capacity	1 + (5/7)
LxBxH (mm)	4450x1200x1950
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	145x80x12
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	6000 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Golf Cart 10S

Specifications

Seating Capacity	1+9
LxBxH (mm)	5250x1200x1950
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	145x80x12
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	7200 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Vintage Buggy 2S/4S

Specifications

Seating Capacity	1 + (1/3)
LxBxH (mm)	3350x1300x1950
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	145x80x12
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	4500 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Vintage Buggy 6S

Specifications

Seating Capacity	1+5
LxBxH (mm)	4250x1300x1950
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	145x80x12
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	5800 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Vintage Buggy 8S

Specifications

Seating Capacity	1+7
LxBxH (mm)	5200x1300x1950
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	145x80x12
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	7200 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Electric Bus 12S

Specifications

Seating Capacity	1+11
LxBxH (mm)	4400x1500x2000
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	145x80x12
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	6000 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Electric Bus 15S

Specifications

Seating Capacity	1 + 14
LxBxH (mm)	5300x1500x2000
Batteries	Lead Acid / LiFePO4
Charger	60/72V, 15 Ah
Drive Motor	60/72V PMSM Motor
Controller	Datai
Breaking System	Hydraulic Oil
Steering	Rack & Pinion
Top Speed	25 Kmph
Range	40-50 Km/Charge
Body Type	FRP
Wheel Size	165x65x14
Tyres	Kelly / CEAT
Gradability	< 25 Degree
Turning Radius	7500 mm
Ground Clearance	180 mm



Chaitanya EV



www.chaitanyaev.in

Electric Loader

Specifications

Loading Capacity 500 / 1000 Kg

Trolley LxBxH (mm) 1800x1200x450

Batteries Lead Acid / LiFePO4

Charger 60/72V, 15 Ah

Drive Motor 60/72V PMSM Motor

Controller Datai

Breaking System Hydraulic Oil

Steering Rack & Pinion

Top Speed 25 Kmph

Range 40-50 Km/Charge

Body Type FRP

Wheel Size 145x80x12

Tyres Kelly / CEAT

Gradability < 25 Degree

Turning Radius 4500 mm

Ground Clearance 180 mm



Chaitanya EV



www.chaitanyaev.in

Electric Garbage Loader

Specifications

Loading Capacity 500 / 1000 Kg

Trolley LxBxH (mm) 1900x1400x900

Batteries Lead Acid / LiFePO4

Charger 60/72V, 15 Ah

Drive Motor 60/72V PMSM Motor

Controller Datai

Breaking System Hydraulic Oil

Steering Rack & Pinion

Top Speed 25 Kmph

Range 40-50 Km/Charge

Body Type FRP

Wheel Size 145x80x12

Tyres Kelly / CEAT

Gradability < 25 Degree

Turning Radius 5000 mm

Ground Clearance 180 mm



Chaitanya EV



www.chaitanyaev.in